

Shaft Supports - Flanged Slit (Cast Type) - Long Sleeve






- **Features:** Longer sleeve than standard type enhances strength against falling
- **Long Sleeve**



Type	M Material	S Surface Treatment	A Accessory
DSHFTL	S45C	Black Oxide	Hex Socket Head Cap Screw 2 pcs.
DSHFML	Equivalent	Electroless Nickel Plating	
DSHFSSL	SUS304 Equivalent	—	Hex Socket Head Cap Screw 2 pcs. (SUS)
DSHFL	AC7A	Clear Anodize	
DSHFDL		Black Anodize	Hex Socket Head Cap Screw 2 pcs.

● D dimension 8 and 10 come with 1 screw.

● Slit is machined after the mounting hole D is bored to H7 tolerance. The tolerance may become H8 or so depending on the machining condition.



√(25/ 63/)

Part Number		L	T	t	H	A	L ₁	d	d ₁	D ₁	t ₁	B	C	h	G	F	Tightening Screw M	Mass g				
Type	D																					
D8~50 DSHFTL DSHFML DSHFSSL DSHFL D8~13, 16~30 DSHFDL	8	43	20	5	25.5	20	32	5.5	10	10	1.5	18	2	10.5	10	-	M5	51(18)				
	10									12								47(17)				
	12	47	28	7	28	25	36		9	14	2.5			11	7	14	M4	91(32)				
	13									16								87(30)				
	15	50	32	8	31	28	40	7	10	20	2	22	2.5	12.5	8	16	M5	114(41)				
	16									24								112(39)				
	20	60	40	10	37	34	48			24				3	22	2.5		15	10	20	M6	191(66)
	25	70	50		42	40	56			30												17
	30	80	60		12	50	46	64	9	12	35	21	15				30	450(156)				
	35	92	70		14	58	50	72	15	40	25.5	17.5	35				M8	592(205)				
	40	102	80	16	67	56	80	12	18	45	30	20	40	M10	831(288)							
	50	122	90	19	83	70	96	14	20	55	38	22.5	45	M12	1446(410)							

● Values in () are the mass for aluminum products.

Basic Specifications

- **Shape** : Flanged Type
- **Flange Shape/Type** : Long Sleeve
- **Clamp Lever** : N/A
- **Shaft Securing Method** : Slit
- **Thickness** : Standard
- **Type** : Cast Product
- **Dowel Hole** : N/A

ORDERING GUIDE



DSHFTL16

www.dymextech.com

india@dymextech.com