

One End Tapped

Air Vent Depth
All air vents are identical in depth.
0.15 ± 0.05

- When D=5 or 6 and L=10, the pilot hole for tapping may go through.
- * l=6 only when D=6 and L=10
- l1, l2 dimension may become larger than the value shown in the catalog due to polishing process.

Type	D Tolerance	Material	Hardness
DMST	p6	SUJ2	45~50HRC
DMSTM	m6		
DMSTMS		SUS440C	

Part Number		ℓ1	ℓ2	M x P	ℓ	Dp6	L										
Type	D																
DMST (p6 Type)	5	1.5	0.5	3 x 0.5	6	+0.020 +0.012	10	15	20	25	30						
	6	2.0		4 x 0.7	*8	+0.024 +0.015	10	15	20	25	30	35	40	50			
	8		5 x 0.8	15			20	25	30	35	40	45	50	60	70	80	
	10	2.5	1.0	6 x 1.0	10	+0.029 +0.018	15	20	25	30	35	40	45	50	60	70	80
	12			8 x 1.25	15		20	30	40	50	60	70	80				
	13	3.0	1.5	8 x 1.25	15	+0.035 +0.022	40	50	60	70	80						
	16			10 x 1.5	18		50	60	70	80							
	20																

Part Number		ℓ1	ℓ2	M x P	ℓ	Dp6	L										
Type	D																
DMSTM (m6 Type)	5	1.5	0.3	3 x 0.5	6	+0.012 +0.004	10	15	20	25	30						
	6	2.0		4 x 0.7	*8	+0.015 +0.006	10	15	20	25	30	35	40	50			
	8		5 x 0.8	15			20	25	30	35	40	45	50	60	70	80	
	10	2.5	1.0	6 x 1.0	10	+0.018 +0.007	15	20	25	30	35	40	45	50	60	70	80
	12			8 x 1.25	15		20	30	40	50	60	70	80				
	13	3.0	1.5	8 x 1.25	15	+0.021 +0.008	40	50	60	70	80						
	16			10 x 1.5	18		50	60	70	80							
	20																

DMST, DMSTM For orders of 1 - 9 pc(s): Unit Price + Low Quantity Surcharge (1 Line Item)

Part Number		ℓ1	ℓ2	M x P	ℓ	Dp6	L					
Type	D											
DMSTM (m6 Type)	5	1.5	0.3	3 x 0.5	*8	+0.012 +0.004	10	15	20			
	6			4 x 0.7			10	15	20	25	30	
	8	2.0	0.5	5 x 0.8	*8	+0.015 +0.006	15	20	25	30	35	40
	10			6 x 1.0			15	20	25	30	35	

Basic Specifications

- **Shaft Dia. Tolerance** - Positive Tolerance
- **Sales Unit** - Low Quantity (Available beginning with 1 pc.)
- **Air Vent** - Provided
- **Shape** - Straight / Dual-Fit Dowel
- **End Shape** - Both Sides Tapered
- **Threading Y/N** - Threading Y/N
- **Tapped Hole** - One Side Tapped

